

PDV15CE2

Plug
& play



LCD Size	15" <i>(également disponible en 17" et 19")</i>
Input Interface	LVDS
Max Resolution	1024X768
Brightness	250 cd/m ²
Contrast Ratio	500 : 1
Display colors	16.2M colors
CPU	Intel® ATOM Processor N270, 1.6GHz Single Core with HT
Chipset	Intel® 945GSE+ ICH7M
Graphic	CRT integrated in 945GSE - D-sub connector LVDS Panel Interface Support panel resolution from VGA through UXGA (1600×1200) Support Dual Channel LVDS panel 24 bit
Memory Type	Non-ECC DDR2 memory running at 533/400 Mhz
Memory Capacity	1× DDR2 SO-DIMM slots supports up to 1GB of memory
I/O Ports	1× VGA ; 1× RS232 COM Port ; 1× Giga Lan ; 4× USB 2.0 ; 1× Audio Out ; 1× Mic In ; 1× Power Jack
IDE / SATA	1× PATA port ; 2× SATA ports
Audio	Class D 3W+3W Amplifier
Extension	1× Mini-PCIe socket ; 1× Compact Flash (Type III)
Power Adapter	80W Power Adapter
OSD function	LCD ON/OFF ; Brightness Control +/- ; Volume Control +/-
LED Function	1× LED on Front Panel for Power ON/OFF
Power Consumption	TBD
Mounting	VESA 100×100
Dimension (W×H×D)	TBD
Temperature	0~40 °C
N/G Weight	TBD
Safety & EMI	CE/FCC
Option	Touch Screen 5 Wire Resistive (Touch controller IC is on board PenMount 6000)
Wireless module	PCIe interface 802.11 a/b/g/n Intel wireless module